



- 1 #30 DOUBLE WASHED PLASTER SAND SUPPLIED BY OGLEBAY NORTON. SUBMIT SAMPLE TO THE COMMUNITY SERVICES FACILITIES AND MAINTENANCE SUPERINTENDENT FOR APPROVAL.
- 2 RESILIENT ACCESSIBLE PROTECTIVE SURFACING TAPERED EDGE TREATMENT ALL AROUND. REFER TO CONST. NOTES SHEET. THICKNESS TO BE AS SPECIFIED BY MANUFACTURER. SUBMIT COLOR/THICKNESS SAMPLE FOR REVIEW/APPROVAL PRIOR TO ORDERING.
- 3 COMPACTED SUBGRADE PER STRUCTURAL SOILS REPORT.
- 4 4" MIN. THICKNESS 4500 P.S.I. @ 28 DAYS CONC. SUBSLAB W/#3 @ 18" O.C. EACH

- WAY @ CENTER OF SLAB. THICKENED EDGE W/2-#4 BARS CONTINUOUS.
- 5 SUB-GRADE TO DRAIN PER CIVIL ENG. PLANS @ 3% MIN. TO PERF. DRAIN LINE. REFER TO CIVIL ENG. PLANS.
- 6 6" THICKENED EDGE W/ 2 #4 BARS CONT. AS SHOWN ON PLAN. 2500 P.S.I. @ 28 DAYS.
- 7 THIOKOL JOINT/JOIN FLUSH
- 8 AT WALK SURROUNDING PLAYGROUND. INSTALL 6" EDGE W/3 #3 BARS CONT. AS SHOWN. APPLY 1/2" RADIUS NOSE ALL EXPOSED EDGES CONT. TYP.
- 9 ADJ CONC. PAVING PER PEDESTRIAN CONC. PAVING DETAIL.
- 10 KEYWAY APPROXIMATELY 3"X3" DEPENDING UPON RESILIENT SURFACE THICKNESS. SPECIFIED BY MANUFACTURER.